



Standard Specification for Drycleaning-Grade Perchloroethylene¹

This standard is issued under the fixed designation D 4081; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This specification covers drycleaning-grade perchloroethylene suitable for use in the drycleaning industry.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

NOTE 1—Practice D 3844 provides additional important information on proper labeling.

2. Referenced Documents

2.1 ASTM Standards:

D 1078 Test Method for Distillation Range of Volatile Organic Liquids²

D 2109 Test Methods for Nonvolatile Matter in Halogenated Organic Solvents and Their Admixtures³

D 2111 Test Methods for Specific Gravity of Halogenated Organic Solvents and Their Admixtures³

D 2942 Test Method for Total Acid Acceptance of Halogenated Organic Solvents (Nonreflux Method)³

D 3316 Test Method for Stability of Perchloroethylene with Copper³

D 3401 Test Methods for Water in Halogenated Organic Solvents and Their Admixtures³

D 3741 Test Method for Appearance of Admixtures Con-

taining Halogenated Organic Solvents³

D 3844 Practice for Labeling Halogenated Hydrocarbon Solvent Containers³

D 4376 Specification for Vapor-Degreasing Grade Perchloroethylene³

D 4494 Test Method for Detecting Residual Odor in Drycleaning Grade Perchloroethylene³

2.2 *Code of Federal Regulations:*⁴

29 CFR 1910.1200 Department of Labor, OSHA Regulations on Hazard Communications

49 CFR 100 to 199 Department of Transportation Hazardous Materials Regulations

3. Properties

3.1 Drycleaning-grade perchloroethylene shall conform to the requirements prescribed in Table 1.

3.2 Maximum acid acceptance specification of 0.03 weight % as NaOH distinguishes drycleaning-grade perchloroethylene from vapor-degreasing-grade perchloroethylene which is formulated specifically for that application.

4. Packaging and Package Marking

4.1 Package and label industrial or commercial quantities in accordance with DOT regulations 49 CFR 100 to 199, and in accordance with state and local regulations, and with OSHA regulations found in 29 CFR 1910.1200.

4.1.1 The proper shipping name for perchloroethylene is UN 1897, tetrachloroethylene.

5. Keywords

5.1 perchloroethylene; tetrachloroethylene drycleaning solvent

⁴ The *Code of Federal Regulations* may be obtained from the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

¹ This specification is under the jurisdiction of ASTM Committee D26 on Halogenated Organic Solvents and Fire Extinguishing Agents and is the direct responsibility of Subcommittee D26.06 on Drycleaning.

Current edition approved June 10, 2000. Published September 2000. Originally published as D 4081 – 82. Last previous edition D 4081 – 95.

² *Annual Book of ASTM Standards*, Vol 06.04.

³ *Annual Book of ASTM Standards*, Vol 15.05.

TABLE 1 Properties

Property	Specification	Test Method
Appearance	clear and free from suspended matter and undissolved water	D 3741
Water, weight, %, max	0.0050	D 3401
Residual odor	no foreign odor	D 4494
Specific gravity, 25/25°C	1.615 to 1.625	D 2111
Nonvolatile residue, weight, %, max	0.0050	D 2109
Distillation range (760 mm Hg)		D 1078
Initial boiling point, °C, min	120.0	
Dry point, °C, max	122.0	
Acid Acceptance (as NaOH), weight %, max	0.03	D 2942
Copper corrosion, weight loss, mg, max		D 3316
Flask	10	
Soxhlet	20	
Condenser	20	
Acidity as HCl, max, mL, NaOH	15	

APPENDIX

(Nonmandatory Information)

X1. PURITY OF PERCHLOROETHYLENE

X1.1 The analysis of perchloroethylene samples taken from drycleaning machines having significant corrosion problems suggests that there may be a relationship between this corro-

sion and the presence of certain halogenated impurities in the solvent. A guideline of 500 ppm (max) 1,1,1 trichloroethane as a contaminant in perchloroethylene is recommended.

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).