



# Standard Specification for Vapor-Degreasing Grade Perchloroethylene<sup>1</sup>

This standard is issued under the fixed designation D 4376; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

## 1. Scope \*

1.1 This specification covers vapor-degreasing grade perchloroethylene.<sup>2</sup>

NOTE 1—Practices D 3844 and D 4276, and provide additional important information on solvent properties.

## 2. Referenced Documents

### 2.1 ASTM Standards:

- D 1078 Test Method for Distillation Range of Volatile Organic Liquids<sup>3</sup>
- D 2108 Test Method for Color of Halogenated Organic Solvents and Their Admixtures (Platinum-Cobalt Scale)<sup>4</sup>
- D 2109 Test Methods for Nonvolatile Matter in Halogenated Organic Solvents and Their Admixtures<sup>4</sup>
- D 2111 Test Methods for Specific Gravity of Halogenated Organic Solvents and Their Admixtures<sup>4</sup>
- D 2942 Test Method for Total Acid Acceptance of Halogenated Organic Solvents (Nonreflux Method)<sup>4</sup>
- D 2988 Test Method for Water-Soluble Halide Ion in Halogenated Organic Solvents and Their Admixtures<sup>4</sup>
- D 2989 Test Method for Acidity-Alkalinity of Halogenated

Organic Solvents and Their Admixtures<sup>4</sup>

D 3316 Test Method for Stability of Perchloroethylene with Copper<sup>4</sup>

D 3401 Test Method for Water in Halogenated Organic Solvents and Their Admixtures<sup>4</sup>

D 3741 Test Method for Appearance of Admixtures Containing Halogenated Organic Solvents<sup>4</sup>

D 3844 Practice for Labeling Halogenated Hydrocarbon Solvent Containers<sup>4</sup>

D 4276 Practice for Confined Area Entry<sup>4</sup>

### 2.2 Other Documents:

49 CFR 100 to 199 Department of Transportation Hazardous Materials Regulations<sup>5</sup>

29 CFR 1919.1200 Department of Labor, OSHA Regulations on Hazard Communications<sup>5</sup>

## 3. Properties

3.1 Vapor-degreasing grade perchloroethylene shall conform to the requirements prescribed in Table 1.

## 4. Packaging and Package Marking

4.1 Package and label industrial or commercial quantities in accordance with DOT regulations 49 CFR 100 to 199, and in accordance with state and local regulations, and with OSHA regulations found in 29 CFR 1910.1200.

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee D-26 on Halogenated Organic Solvents and Fire Extinguishing Agents and is the direct responsibility of Subcommittee D26.02 on Vapor Degreasing.

Current edition approved Dec. 10, 1998. Published March 1999. Originally published as D 4376 – 84. Last previous edition D 4376 – 94.

<sup>2</sup> Contains inhibitors.

<sup>3</sup> *Annual Book of ASTM Standards*, Vol 06.04.

<sup>4</sup> *Annual Book of ASTM Standards*, Vol 15.05.

<sup>5</sup> The *Code of Federal Regulations* may be obtained from the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

**TABLE 1 Physical Properties**

Property	Specification	Test Method
Specific gravity, 25/25°C	1.610 to 1.625	D 2111
Distillation range (760 mm Hg)		D 1078
Initial boiling point, °C, min	120.0	
Dry point, °C, max	125.0	
Acidity (as HCl), weight, %, max	0.0005	D 2989
Alkalinity (as NaOH), weight, %, max	0.030	D 2989
Water, weight, %, max	0.0050	D 3401
Appearance	Clear and free from suspended matter	D 3741
Color, Pt-Co, max	20	D 2108
Halide (as Cl <sup>-</sup> ), weight, %, max	0.0005	D 2988
Nonvolatile residue, weight, %, max	0.0050	D 2109
Acid acceptance, as NaOH, weight, %, min	0.10	D 2942
Copper corrosion, weight loss, mg, max		D 3316
Flask	10	
Soxhlet	20	
Condenser	20	
Acidity as HCl, max, mL, NaOH	15	

## 5. Keywords

5.1 perchloroethylene; tetrachloroethylene; vapor degreasing

## SUMMARY OF CHANGES

This section identifies the location of changes to this standard that have been incorporated since the –84(90)<sup>e1</sup> issue. Committee D-26 has highlighted those changes that affect the technical interpretation or use of this standard.

- (1) Added Test Method D 3741 to Section 2 “Referenced Documents”.
- (2) Deletion of packaging requirements for Department of Defense (DoD) procurements. This deletion has been requested by DoD for similar Specifications D 4080 and D 5960.
- (3) Added reference to OSHA package marking requirements.

This same language has been adopted for similar Specifications D 4701 and D 5960.

- (4) Deletion of references to the Vapor Degreasing and Cold Cleaning Manuals. Both of these publications are out of print, and will not be republished.

*The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 100 Barr Harbor Drive, West Conshohocken, PA 19428.*