



# Standard Test Method for Detecting Residual Odor of Drycleaning Grade Perchloroethylene<sup>1</sup>

This standard is issued under the fixed designation D 4494; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 This test method covers the detection of a residual odor in drycleaning-grade perchloroethylene.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* Specific precautionary statements are given in Section 7.

## 2. Referenced Documents

### 2.1 ASTM Standards:

D 3844 Practice for Labeling Halogenated Hydrocarbon Solvent Containers<sup>2</sup>

## 3. Summary of Test Method

3.1 A swatch of conditioned cotton fabric is treated by soaking in drycleaning perchloroethylene, then drained, dried, and steamed. The odor is compared with an untreated swatch. The treated swatch should be no different from the untreated.

## 4. Significance and Use

4.1 Normally clothes cleaned with perchloroethylene will have a clean cloth odor. If a foreign odor is present, it may be objectionable.

## 5. Apparatus

5.1 *Two-Glass Beakers*, 1 L.

5.2 *Oven*, forced convection model.

## 6. Material

6.1 De-sized and bleached cotton fabric weighing from 120

to 135 g/m<sup>2</sup> (3.6 to 4.0 oz/yd<sup>2</sup>). The fabric shall be clean, dry, and free from foreign odor.

## 7. Safe Handling Precautions

7.1 Handle perchloroethylene only in a well-ventilated hood for conducting the test. See Practice D 3844 for the label information.

## 8. Procedure

8.1 Condition a swatch, 300 by 300-mm (12 by 12-in.) size, of test fabric at 60 ± 10 % relative humidity for at least 8 h.

8.2 Soak the test swatch in a beaker with 100 mL of perchloroethylene for 5 min.

8.3 Remove it from the beaker and allow to drain and dry at room temperature for 4 h.

8.4 Dry the treated swatch in a fresh air oven at 60°C (140°F) for 30 min.

8.5 Place the treated swatch in the steam vapor from boiling water for 5 s and check the odor of the cloth.

8.6 Compare the odor of the treated swatch with an untreated control swatch, that was subjected to all steps of the test except 8.2 and 8.3.

## 9. Report

9.1 Report whether the treated sample cloth has a detectable foreign odor or no foreign odor.

## 10. Precision and Bias

10.1 No statement is made about either the precision or the bias of Test Method D 4494 for measuring residual odor since the result merely states whether there is conformance to the criteria for success specified in the procedure.

## 11. Keywords

11.1 drycleaning; perchloroethylene; residual odor

<sup>1</sup> This test method is under the jurisdiction of ASTM Committee D26 on Halogenated Organic Solvents and Fire Extinguishing Agents and is the direct responsibility of Subcommittee D26.04 on Test Methods.

Current edition approved Sept. 10, 1995. Published November 1995. Originally published as D 4494 – 85. Last previous edition D 4494 – 85 (1991) $\epsilon$ <sup>1</sup>.

<sup>2</sup> *Annual Book of ASTM Standards*, Vol 15.05.

 **D 4494**

*The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or [service@astm.org](mailto:service@astm.org) (e-mail); or through the ASTM website ([www.astm.org](http://www.astm.org)).*