



# Standard Specification for Acetaldehyde<sup>1</sup>

This standard is issued under the fixed designation D 4710; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope \*

- 1.1 This specification covers acetaldehyde (99 % grade).
- 1.2 The following applies to all specified limits in this standard; for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E 29.
- 1.3 For specific hazard information and guidance, see the supplier’s Material Safety Data Sheet for materials listed in this specification.

## 2. Referenced Documents

- 2.1 *ASTM Standards*:
  - D 1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)<sup>2</sup>
  - D 1353 Test Method for Nonvolatile Matter in Volatile Solvents for Use in Paint, Varnish, Lacquer, and Related Products<sup>2</sup>
  - D 2086 Test Method for Acidity in Vinyl Acetate and Acetaldehyde<sup>2</sup>
  - D 2192 Test Method for Purity of Aldehydes and Ketones<sup>2</sup>
  - E 29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications<sup>3</sup>
  - E 300 Practice for Sampling Industrial Chemicals<sup>4</sup>
- 2.2 *U.S. Federal Specification*:

PPP-C-2020 Chemicals, Liquid, Dry, and Paste: Packaging of<sup>5</sup>

## 3. Properties

3.1 Acetaldehyde shall conform to the following requirements:

Purity, wt %, min, as acetaldehyde	99
Color, Pt-Co units, max	15
Acidity, wt %, max, (free acid as acetic acid)	0.05
Nonvolatile matter, wt %, max	0.5

## 4. Sampling

4.1 The material shall be sampled in accordance with Practice E 300.

## 5. Test Methods

5.1 The properties enumerated in this specification shall be determined in accordance with the following ASTM test methods:

- 5.1.1 *Purity*—Test Method D 2192.
- 5.1.2 *Color*—Test Method D 1209.
- 5.1.3 *Acidity*—Test Method D 2086.

5.1.4 *Nonvolatile Matter*—Determine the nonvolatile matter or residue after evaporation in accordance with Test Method D 1353 except use an oven temperature of  $60 \pm 5^\circ\text{F}$ .

## 6. Packaging and Package Marking

- 6.1 Package size shall be agreed upon between the purchaser and the supplier.
- 6.2 Packaging shall conform to applicable carrier rules and regulations or when specified shall conform to Fed. Spec. PPP-C-2020.

## 7. Keywords

7.1 acetaldehyde; acidity; aldehyde

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.35 on Solvents, Plasticizers, and Chemical Intermediates.

Current edition approved July 10, 2002. Published September 2002. Originally published as D 4710 – 87. Last previous edition D 4710 – 93 (1999).

<sup>2</sup> *Annual Book of ASTM Standards*, Vol 06.04.

<sup>3</sup> *Annual Book of ASTM Standards*, Vol 14.02.

<sup>4</sup> Discontinued; see *2001 Annual Book of ASTM Standards*, Vol 15.05.

<sup>5</sup> Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098.

\*A Summary of Changes section appears at the end of this standard.

**SUMMARY OF CHANGES**

Committee D01.35 has identified the location of selected changes to this standard since the last issue (D 4710 - 93 (1999)) that may impact the use of this standard.

(1) Added reference to Practice E 29 in Scope section.

(2) Added Practice E 29 to list of Referenced Documents.

*ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or [service@astm.org](mailto:service@astm.org) (e-mail); or through the ASTM website ([www.astm.org](http://www.astm.org)).*