



Standard Specification for Technical Grade Ethylene Dichloride¹

This standard is issued under the fixed designation D 5960; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers technical grade ethylene dichloride.

2. Referenced Documents

2.1 ASTM Standards:

D 2108 Test Method for Color of Halogenated Organic Solvents and Their Admixtures (Platinum-Cobalt Scale)²

D 2111 Test Methods for Specific Gravity of Halogenated Organic Solvents and Their Admixtures²

D 2989 Test Method for Acidity-Alkalinity of Halogenated Organic Solvents and Their Admixtures²

D 3401 Test Methods for Water in Halogenated Organic Solvents and Their Admixtures²

D 3447 Test Method for Purity of Halogenated Organic Solvents²

D 3844 Practice for Labeling Halogenated Hydrocarbon Solvent Containers²

D 4276 Practice for Confined Area Entry²

2.2 U. S. Government Documents:

TABLE 1 Technical Grade Ethylene Dichloride Requirements

Property	Specification	Test Method
Color, Pt-Co, max	10	D 2108
Ethylene Dichloride, Weight %, min	99.8	D 3447
Specific Gravity, 25/25°C	1.248–1.252	D 2111
Acidity (as HCl), ppm, max	10	D 2989
Water, ppm, max	200	D 3401

49 CFR 100 to 199 Department of Transportation Hazardous Materials Regulations³

29 CFR 1919.1200 Department of Labor, OSHA Regulations on Hazard Communications³

3. Chemical Composition

3.1 Technical grade ethylene dichloride shall conform to the requirements prescribed in Table 1.

4. Packaging and Package Marking

4.1 Package and label industrial or commercial quantities in accordance with DOT regulations 49 CFR 100 to 199, and in accordance with state and local regulations, and with OSHA regulations found in 29 CFR 1910.1200.

5. Keywords

5.1 ethylene dichloride; 1,2-dichloroethane

¹ This specification is under the jurisdiction of ASTM Committee D26 on Halogenated Organic Solvents and Fire Extinguishing Agents and is the direct responsibility of Subcommittee D26.02 on Vapor Degreasing.

Current edition approved May 10, 1997. Published May 1998.

² *Annual Book of ASTM Standards*, Vol 15.05.

³ The Code of Federal Regulations may be obtained from the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).